



# Eco 360 Comfort Plus 2:1 Punch / Closer

## Wire Punch/Closers

The ECO 360 Comfort wire binding machine is an entry level electric punch and manual wire closer. The PDC ECO 360 Comfort punches 2:1" pitch square holes. With selectable punching pins and adjustable punch margin the ECO 360 Comfort offers complete flexibility when punching a range of paper sizes and weights.

For 3:1" punching the PDC SRW 360 Comfort should be used or alternatively, why not try our unique one pitch 2:1" wire and use your PDC ECO 360 Comfort to bind documents from 3 to 240 pages without the need for an additional punch.



## Features and Benefits

- **Vertical Punching Throat:** Utilizes gravity to align various sheet sizes in the punching throat, eliminating punching skew.
- **Adjustable Edge Guide:** Adjustable to ensure accurate alignment of paper.
- **Selectable Punch Pins:** Punch pins can be deselected to accommodate most paper sizes.
- **Adjustable Punch Margin:** A selector dial allows punched margins to be increased or decreased according to the document size.
- **Integral Wire Closer:** The RENZ ECO 360 Comfort is fitted with an integral wire closer for all wire sizes.
- **Wire Clamp Holder:** The RENZ ECO 360 Comfort is fitted with a wire holding bar, allowing the operator to punch and load the paper onto the wire easily.
- **Front Loading Chip Tray:** Large front loading chip tray provides easy access for emptying chips.
- **All Metal Construction:** Solid castings provide greater punching durability.
- **Binding Capacity:** Will bind a maximum of 425 sheets of 80gsm paper.

## Technical Specification

Dimensions	430 x 560 x 180 mm
Weight	26 kg
Power Requirements	230/250V / 50Hz / 180W 115/200V / 60Hz / 180W
Punching capacity - sheets per hr	16,000
Min. punching width	10 mm
Max. punching width	360 mm
Min. unpunched length	50 mm
Max. unpunched length	500 mm
Max. punching thickness	2.5 mm
Punching operation	Electric
Punch pattern	Oblong 5.5 x 3.5 mm
Pitch	2:1
Selectable punch pins (QSA)	Yes
Variable margin depth	Yes
Binding Thickness	1 - 34 mm
Binding element Ø	6,9 - 38 mm 1/4" - 1 1/2"
Min. binding width	10 mm
Max. binding width	360 mm
Binding Operation	Manual
No. of books/ calendars output per hr	250 / 180